

Tele: 23793509

Policy Letter No 30/2012
Directorate General Married
Accommodation Project (DG MAP)
Engineer-in-Chief's Branch,
Integrated HQ of MoD (Army)
Kashmir House, Rajaji Marg,
DHQ PO, New Delhi-110011

21379/Spec Ph-III/P&S/29/MAP

23 Jul 2012

(All PMs & DEPMCs)

SPECIFICATIONS: OIL BOUND DISTEMPER

1. Refer this Headquarters letter No 21378/Vendor PH-III/P&S/03/MAP dt 29 Jun 2012
2. Given in the succeeding sub paragraphs are the specifications for Oil Bound Distemper for the future projects of MAP Phase-II & Phase-III:-

(a) **Preparation of new surfaces:** The surface shall be thoroughly cleaned of dust, dirt, efflorescence, chalking, grease, mortar drops and other foreign matter. The surface shall be sand papered with grade I abrasive paper and dusted off to achieve an even and smooth surface. If surface so obtained is uneven, it shall be brought to a perfectly even surface by applying cement based wall putty and allowing it to dry completely and then it shall be rubbed with the abrasive paper and dusted off all as specified in clause 15.13.1 on serial page 324 of SSR Part-I.

(b) **Oil Bound Distemper:** Oil bound distemper Acrylic to all internal walls of all Offrs, JCO/OR DUs shall be provided with two coats of oil bound distemper Acrylic over a coat of cement primer manufactured by reputed firms as mentioned in the list of approved makes/ and shall conform to I S: 428-2000 & shall be provide over prepared surface as specified in clause 15.14 on serial page 325 & 326 of SSR Part-I. To obtain a better finish and longer durability co-polymer based resin glue will be added to the prepared distemper solution.

(JS Sodhi)
Lt Col
SO 1 (P&S)
for DG MAP

Internal

Team 'A'	-	for necessary action please
Team 'B'	-	-do-
Contract Section Team 'A'	-	-do-
Contract Section Team 'B'	-	-do-
Arch Section	-	-do-